

Transmission Laser Modules

Key Features

7-pin Low Profile package with GPO connector RF input

High frequency RF connector package with 50Ω RF impedance

InGaAsP monolithically integrated DFB laser and modulator chip

High output power:
 $P_{AVE} \geq 2$ dBm

Low drive voltage (≤ 2 Vpp)

Very low dispersion penalty up to 90 km for 10.7 Gbit/s operation (up to 1600 ps/nm)

RoHs Compliant

Applications

Metro SONET/SDH equipment

STM-64 (S64.2) and OC-192 (LR-2)
SFF 300-pin MSA Transceiver

10 GbE 300-pin MSA Transponder

For more info

Please contact us at:

North America: 514.748.4848
888.922.1044


Europe & Asia: +33 (0) 1 69 80 58 33
or via e-mail at sales@3spgroup.com

1915 LMM TDM HP

TDM - 1600 ps/nm application - ≥ 2 dBm average output power 10.7 Gbit/s digital Laser Module with Integrated Electro-Absorption Modulator

The 1915 LMM contains a 3SPGroup DFB laser with monolithically integrated electro-absorption modulator (EA-ILM).

The modulation voltage is applied to the modulator section while the DFB laser operates CW. Without the complexity of LiNbO3 external modulators, the 1915 LMM is dedicated to STM64/OC-192 bit rate with reduced size and reduced cost. This device allows 10.7 Gbit/s data transmission with an extinction ratio higher than 10dB and less than 2V modulation voltage.



1915 LMM TDM HP

**TDM - 1600 ps/nm application
- ≥ 2 dBm average output
power 10.7 Gbit/s digital
Laser Module with Integrated
Electro-Absorption Modulator**



OPTICAL CHARACTERISTICS

Parameters	Symb	Conditions	Min	Max	Units
Operating case temperature	Tc		-5	75	°C
Threshold current	I _{th}	CW	5	35	mA
Operating current	I _f	CW	80	100	mA
Optical output power	P _{ave}	I _f , V _{mod} , [1], [2]	2	6	dBm
Laser forward voltage	V _f	CW, I _f , V _{bias} = 0V		2	V
ON state voltage	V _{on}	See [1]	-1	0	V
Modulator bias voltage	V _{bias}	See [1]	-2		V
Modulator drive voltage	V _{mod}	See [1]		2	V
Dynamic extinction ratio	DER	I _f , [1], [2]	10		dB
Emission wavelength	λ		1530	1570	nm
Side mode suppression	SMSR	See [1]	40		DB
Relative intensity noise	RIN	100 MHz to 9 GHz, @ P _{ave}		-130	dB/Hz
Cut off frequency	S ₂₁	- 3 dB, V _{bias} @ I _f	9		GHz
RF return loss	S ₁₁	DC to 7 GHz	10		DB
	S ₁₁	7 to 10 GHz		7	DB
Dispersion penalty	λS	See [1], [2]		2	DB
Rise time / Fall time	Tr/Tf	See [1], 10%, 90%		45	ps
Monitor diode current	I _m	I _f , V = - 5 V	20	1500	μ A
Monitor diode dark current	I _d	I _f , V = - 5 V		0,1	μ A
Monitor diode capacitance	C _m	@ 1MHz, V = -5 V		15	pF
TEC current	I _t	$\Delta T= 50^{\circ}\text{C}$, I _f +20% (EOL), V _{bias} = - 1V		1.4	A
TEC voltage	V _t	$\Delta T= 50^{\circ}\text{C}$, I _f +20% (EOL), V _{bias} = - 1V		2.5	V
Thermistor resistance	R _{TH}	T _{submount} = 25°C	9.5	10.5	k Ω
Thermistor β coefficient	β	T _{submount} = 25°C	3800	4000	K

Notes : All limits start of life T_{case} in the range [-5°C; 75°C], T_{submount}= 25°C, monitor bias= - 5 V, unless otherwise stated.

[1] BER= 10-10; 10.7 Gbit/s modulation; 231-1 PRBS; NZR line code

[2] 1600 ps/nm dispersion assuming fiber with an average dispersion of 18 ps/nm/km @ 1550nm

[3] TE= Max { |(P(75°C)-P(25°C))/P(25°C)| ; |(P(-5°C)-P(25°C))/P(25°C)| }

Absolute Maximum Ratings

Parameters	Min	Max	Unit
Operating case temperature	-5	75	°C
Storage temperature	- 40	85	°C
CW optical output power		10	dBm
Laser forward current		150	mA
Laser reverse voltage		2	V
Modulator forward voltage		1	V
Modulator reverse voltage		5	V
Photodiode forward current		1	mA
Photodiode reverse voltage		20	V
TEC voltage		2.8	V
TEC current		1.4	A
ESD applied on PIN detector (pid 4&5, human body model)		100	V
ESD applied on other pins (humand body model)		2000	V
Lead soldering time (at 260°C)		10	s
Fiber bend radius	25		mm
Packing mounting screw torque		0.2	Nm

Exposure to absolute maximum rating conditions for extended periods may affect device reliability.


1915 LMM TDM HP

TDM - 1600 ps/nm application
- ≥ 2 dBm average output
power 10.7 Gbit/s digital
Laser Module with Integrated
Electro-Absorption Modulator




Pin Out

N°	Description
1	Thermistor
2	Thermistor
3	Laser DC bias (+)
4	Photodetector Anode (-)
5	Photodetector Cathode (+)
6	TEC (+)
7	TEC (-)



Mechanical Details



Dimensions are in mm
Fiber length 1600 ± 100 mm
(including optical connector)

1915 LMM TDM HP

**TDM - 1600 ps/nm application
- ≥ 2 dBm average output
power 10.7 Gbit/s digital
Laser Module with Integrated
Electro-Absorption Modulator**



Shipment **packing**

Each device is individually packed in an anti-static container and in such a manner as to prevent damage in transit.

The packing shall include the following information:

3S Photonics logo
Product family name : 1915 LMM
Product code : 3CN number (see Ordering information section)
Serial number
Hazard warning label (ESD)
Laser Safety Class Label

Laser Safety **Information**

Take appropriate precautions to prevent undue exposure to naked eye.

This product is classified Class 1M Laser Product according to IEC-60825-1: edition2.

All versions are Class IIIB laser products per 21 CFR 1040-10 Laser. Safety requirements under accession number 0120546-00.



Qualification, Reliability and **Standards**

3SPGroup policy for all products is to carry out a complete qualification program. This qualification is based on manufacturers' qualification in agreement with Telcordia GR-468-Core (Generic Reliability Assurance Requirements for Optoelectronic Devices Used In Telecommunications Equipment - Central Office Level), MIL STD 883E (Test method and procedures for microelectronics) and following the standards ITU-T G652 and G-691. All products pass strict tests before shipping. Failure criteria are defined during the product qualification process.

Device **marking**

The device shall be legibly and permanently marked with the following information:

3S Photonics logo
Product family name: 1915 LMM
Product code : 3CN number (see Ordering information section)
Serial number

Deliverable **data**


The following data shall be supplied with each device:

L(I) / V(I) / Im(I) curves
Values for Vmod, Von (On-state voltage [0 data]), Vbias (bias voltage), S0 (received optical power without fiber), SMSR, ITH, It, Vt, I and Pave for If DER and dispersion penalty (DS)
Plot of SER vs Vmod over the range 0 V to -3 V @ If, Tc= 25 °C and Tsubmount=25°C

Handling

This product is sensitive to electrostatic discharge and should not be handled except at a static free workstation. Take precautions to prevent ESD; use wrist straps, grounded work surfaces and recognised anti-static techniques when handling the product. Handle the laser module by its package only, never hold it by its pigtail.

Care should be taken to avoid supply transient and over voltage. Over voltage above the maximum specified in absolute maximum rating section may cause permanent damage to the device.



1915 LMM TDM HP

TDM - 1600 ps/nm application
- ≥ 2 dBm average output
power 10.7 Gbit/s digital
Laser Module with Integrated
Electro-Absorption Modulator



ORDERING INFORMATION

Application	Part number	Electrical Connector	Optical Connector
TDM	3CN01108AR	GPO type	LC/PC

Revised March 2012

Please note: information in this document is typical and must be specifically confirmed in writing by your supplier before it becomes applicable to any order or contract. Information is subject to change without notice.
 ©2011 3S PHOTONICS S.A.S.

ORDERING INFO

Please contact your Sales Manager. 3SPGroup can also develop custom products to meet a wide range of technical requirements.

3SPGroup
 North America: 514.748.4848
 888.922.1044
 Europe and Asia: +33 (0)1 69 80 58 33
www.3spgroup.com • sales@3spgroup.com

