



Key Features

Fast Transient Control

Output Power up to +23 dBm

ROHS Compliant

Uncooled Pump Option

Telcordia Qualified

Gain-Flattened Version for Full-band Amplification

Industry Standard Form Factor (70x90x15mm)

State-of-the-Art Integrated Control Electronics

Applications

Long Haul and Metro Networks

Transmitter and Receiver Amplification

Single Channel, Narrowband and Wideband DWDM

For more info

Please contact us at:

North America: **514.748.4848**
888.922.1044

Europe & Asia: **+33 (0) 2 96 04 20 00**
or via e-mail at sales@3spgroup.com

Compact EDFA with Control Electronics

The Manlight Compact EDFA gain module with integrated control electronics is suitable for DWDM systems where fast transient control and gain flattening is required. It can be optimized to perform as a booster, line and pre-amplifier in systems and subsystems for metro and long haul applications.

It operates in constant gain, constant power mode or in constant current mode. The gain block contains input and output monitor diodes and isolators. The EDFA can be configured to use an uncooled pump laser that enables low power consumption which allows system designers to achieve compact solutions, lower costs and flexibility in system design.



Compact EDFA

with Control Electronics



SPECIFICATIONS*

OPTICAL CHARACTERISTICS

Parameters	Booster Single-Channel	Booster Single-Channel	Gain-Flattened	Unit
Wavelength Range	1529 - 1565	1529 - 1565	1529 - 1565	nm
Maximum Output Power	+23	+5	+20	dBm
Input Power Range	-10 to +4	-30 to -10	-25 to -3	dBm
Nominal Gain	20	30	23	dB
Gain Flatness (typ) @ Nominal Gain	N/A	N/A	0.8	dB
Gain Flatness (max) @ Nominal Gain	N/A	N/A	1.5	dB
Noise Figure (typ) @ Nominal Gain	5.0	5.0	5.0	dB
Noise Figure (max) @ Nominal Gain	5.5	5.5	5.5	dB
Polarization Mode Dispersion	0.3	0.3	0.3	ps
Polarization Dependent Gain	0.3	0.3	0.4	dB

ELECTRICAL & ENVIRONMENTAL CHARACTERISTICS

Transient Settling Time (typ / max)	50 / 200	µs
Transient Overshoot/Undershoot (typ/max)	0.3 / 0.8	dB

Transient Settling Time (typ / max)	50 / 200	µs		
Transient Overshoot/Undershoot (typ/max)	0.3 / 0.8	dB		
Power Consumption (typical / max EOL)	6.0 / 12.0	2.0 / 3.0	6.0 / 12.0	W
Power Consumption (Uncooled version)	2.0 / 3.5	1.5 / 3.0	2.0 / 3.5	W
Power Supply Voltage	+3.3 or +5.0			VDC
Operating Case Temperature	0 to +70			°C
Storage Temperature	-40 to +85			°C
Operating Humidity (non-condensing)	5 - 95			% RH

Pin#	Description	Pin#	Description	Pin#	Description
1	+3.3 V / +5.0 V	11	NC	21	Input Power Mon GND
2	+3.3 V / +5.0 V	12	Reset	22	Output Power Mon GND
3	+3.3 V / +5.0 V	13	Amplifier Disable	23	Input Power Monitor
4	+3.3 V / +5.0 V	14	Output Power Mute	24	Output Power Monitor
5	GND	15	Case Temp Alarm	25	GND
6	GND	16	NC	26	GND
7	RS-232 IN (TTL)	17	Pump Temp. Alarm	27	+3.3 V / +5.0 V
8	RS-232 OUT (TTL)	18	Pump Bias Alarm	28	+3.3 V / +5.0 V
9	GND	19	Loss of Input Alarm	29	+3.3 V / +5.0 V
10	GND	20	Loss of Output Alarm	30	+3.3 V / +5.0 V

Revised March 2012



Please note: information in this document is typical and must be specifically confirmed in writing by your supplier before it becomes applicable to any order or contract. Information is subject to change without notice.

©2011 3S PHOTONICS S.A.S.

ORDERING INFO

Please contact your Sales Manager. 3SPGroup can also develop custom products to meet a wide range of technical requirements.

3SPGroup
North America: 514.748.4848
888.922.1044

Europe and Asia: +33 (0) 2 96 04 20 00
www.3spgroup.com • sales@3spgroup.com