



MULTIMODE COMPONENTS

(6+1) x 1 HIGH POWER Pump and Signal Combiners

ITF Labs' Multimode Pump and Signal Combiners feature exceptional optical characteristics. These devices can be used to combine the power from several multimode laser diodes and couple that power with a signal feed, delivering the combined power for applications in industrial, military, medical and telecommunications markets.

ITF Labs' Multimode Combiners offer efficient power transfer for high power applications like fiber lasers and fiber amplifiers, with a maximum conservation of brightness. The Multimode Combiners can be designed to meet a wide range of power handling configurations, number of input fibers and adaptation to different fiber types.



For more information on this or other products and their availability, please contact our customer service at **514.748.4848** (Int'l) / **1.888.922.1044** (Canada & USA only) or via e-mail at info@itflabs.com

KEY FEATURES

- High Power Transfer Efficiency
- Preservation of Modal Content
- Wavelength Insensitive
- Custom Configurations Available
- RoHS Compliant

MULTIMODE COMPONENTS

(6 + 1) x 1 HIGH POWER Pump and Signal Combiners

SPECIFICATIONS

STANDARD CONFIGURATIONS

Product Code	MMC06112221	MMC06112171	MMC06113221	MMC06113621
Optical Specifications				
Signal Operating Wavelengths	1030-1080 nm	1530-1580 nm	1030-1080 nm	1030-1080 nm
Pump Operating Wavelengths	800-1000 nm	800-1000 nm	800-1000 nm	800-1000 nm
Number of Multimode Inputs	6	6	6	6
Number of Signal Ports	1	1	1	1
Number of DCF Ports	1	1	1	1
Pump Input Fiber core/clad diameter NA	105 µm/125 µm 0.22	105 µm/125 µm 0.22	200 µm/220 µm 0.22	200 µm/220 µm 0.22
Signal Input Fiber core/clad diameter NA	HI 1060 6 µm/125 µm 0.14	SMF-28	HI 1060 6 µm/125 µm 0.14	20 µm/400 µm 0.06/0.46
Output Fiber core/clad diameter NA	20 µm/400 µm 0.06/0.46	20 µm/200 µm 0.11/0.46	20 µm/400 µm 0.06/0.46	20 µm/400 µm 0.06/0.46
Power per Pump Input	50 W	50 W	100 W	100 W
Total Power	300 W	300 W	600 W	600 W
Maximum Pump Insertion Loss	< 0.3 dB	< 0.3 dB	< 0.3 dB	< 0.3 dB
Maximum Signal Insertion Loss	< 0.5 dB	< 0.5 dB	< 0.5 dB	< 0.5 dB
Optical Return Loss	45 dB	45 dB	45 dB	45 dB
Mechanical Specifications				
Length x Width x Height	60 x 12 x 6.5 mm	60 x 12 x 6.5 mm	60 x 12 x 6.5 mm	60 x 12 x 6.5 mm
Fiber Pigtail Length Input/Output	> 750 mm	> 750 mm	> 750 mm	> 750 mm

PATENTED

ORDERING INFORMATION

For standard products, please use product codes specified above.
ITF Labs can also develop custom multimode power combiners to meet
a wide range of technical requirements.



ITF Labs

400 Montpellier Blvd
Montreal, Quebec H4N 2G7 CANADA

Tel: 514.748.4848

Fax: 514.744.2080

1.888.922.1044

www.itflabs.com info@itflabs.com